

Protect Your Underground Investment

Widely used to identify buried structures  
and construction hazard zones

Made to PWA color specifications

Acid and Alkali resistant



**Detectable**



**NonDetectable**



Types			Packaging	
Detectable	NonDetectable	Caution	Size	Rolls/Case
2" x 1000'	2" x 1000'	3" x 1000'	2"	6
3" x 1000'	3" x 1000'		3"	4
6" x 1000'	6" x 1000'		6"	2
12" x 1000'	12" x 1000'		12"	1

## Specifications

### Color Codes

White	Proposed Evacuation
Pink	Temporary Survey Marking
Red	Electric Power Lines, Conduit and Lighting Cables
Yellow	Gas, Oil, Steam, Petroleum or Gaseous Materials
Yellow	Caution
Blue	Potable Water
Purple	Reclaimed Water, Irrigation or Slurry Lines
Orange	Communication, Alarm or Signal Lines, Cables or Conduit
Green	Sewer and Drain Lines
Brown	Force Main

Sherlock Brand Underground and Caution Tapes meet ANSI Z535.1 specifications.

## Physical Properties

Test Data	Method	Detectable Value	NonDetectable Value	Caution Value
Thickness (mil)	ASTM D210	5.0 nominal	4.0 nominal	2.0 nominal
Tensile Strength	ASTM D882	35 lbs/in	10 lbs/in	**
Elongation	ASTM D882-7	60%	600%	**
Printability	ASTM D257	45 Dynes	45 Dynes	**



**SHERLOCK** TAPES  
Protect Your Underground Investment